

Rotating Mixer

FMX-RD-E Product Description:

- ·Provides gentle but effective rolling.
- -Adjustable speed range from 0 to 80 rpm.
- •A wide variety of accessories are available.

FMX-RL-E Product Description:

- Provides gentle and effective mixing of biological samples.
- ·Adjustable speed range from 0 to 80rpm.
- •A wide variety of accessories are available.





-A wide variety of accessories are available. FMX-RL-Pro Product Description:

·LCD display of speed and time.

·Speed range from 10 to 70rpm.

·Electronic adjustment of speed and time.

FMX-RD-Pro Product Description:

·Rolling action, gives gentle but effective mixing.

·Electronic adjustment of speed and time.

-Adjustable mixing angle from 0 to 90°.

- -LCD display speed and time.
- ·Speed range from 10 to 70 rpm.
- -Provides gentle but effective rolling.
- ·A wide variety of accessories are available.







| FIVIX-RL-PRO | | LMY-KD-E | | FINIX-RD-PRO |
|--|-------------------|--------------------|-------------------|--------------------|
| Parameters /Model | FMX-RD-E | FMX-RD-Pro | FMX-RL-E | FMX-RL-Pro |
| Motor type | DC motor | DC motor | DC motor | DC motor |
| Tilt angle | | 0-90° | | |
| Speed range | 0-80rpm | 10-70rpm | 0-80rpm | 10-70rpm |
| Speed display | Scale | LCD | Scale | LCD |
| Timer display | Scale | LCD | Scale | LCD |
| Timer | | 1-1199min | | 1-1199min |
| Operation mode | Continuous | Continuous / timer | Continuous | Continuous / timer |
| Voltage | 100-240V, 50/60Hz | 100-240V, 50/60Hz | 100-240V, 50/60Hz | 100-240V, 50/60Hz |
| Power | 20W | 40W | 20W | 40W |
| Dimension[D×W×H] | 150X530X190mm | 280×210×300mm | 300×220×310mm | 220×510×260mm |
| Permissible ambient temperature and humidity | 5-40oC,80%RH | 5-40oC, 80%RH | 5-40oC, 80%RH | 5-40oC,80%RH |
| Protection class | IP21 | IP21 | IP21 | IP21 |